

NL-82022MP MD6 Serial Multi GNSS UDR Receiver u-blox NEO-M8U 5 m

Leírás

The MD6 serial multi GNSS UDR receiver by Navilock based on u-blox NEO-M8U chipset has a built-in active antenna as well as high-sensitivity sensors such as a 3D accelerometer and a 3D gyroscope. In conjunction with a laptop, a reliable position determination is also possible when the GNSS signal is interrupted. The MD6 universal connector enables the connection of optional USB or serial connecting cables. The NL-82022MP GNSS receiver is especially designed for installation on a white ground (camper, bus etc.) It is unremarkable and fits into the vehicle concept due to its housing design.

Megjegyzés

The manual contains essential installation and commissioning conditions for the successful operation of this GNSS receiver!



Tételszám 62755

EAN: 4043619627554

Származási hely: Taiwan,
Republic Of China

Csomag: Retail Box

Műszaki adatok

- Connector: MD6 Navilock plug (USB or serial cable are optional available)
- Chipset: u-blox NEO-M8U
- Frequency:
 - GPS: L1, 1575.4200 MHz
 - GLONASS: L1, 1602 (k x 0.5625) MHz
 - BEIDOU COMPASS: B1, 1561.0980 MHz
 - GALILEO: E1, 1575.4200 MHz
 - QZSS: L1, 1575.4200 MHz
- Accepts the signals of up to 72 satellites at the same time
- Supports AssistNow online / offline, SBAS (WAAS, EGNOS, QZSS and MSAS)
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
- Supports UDR from NMEA 4.1
- Auto Baud Rate up to 115200 bps
- PPS signal on pin 6
- Update rate: up to 20 Hz
- Sensibility max. -160 dBm
- IPX7 protection class
- Operating temperature: -20 °C ~ 60 °C
- Power supply: 5 - 48 V DC
- Current consumption: max. 45 mA
- Cold start in ca. 26 seconds

- Hot start in ca. 1 second
- Positioning accuracy: 2.5 m CEP (Circular Error Probable) and 2 m CEP with SBAS
- Cable length: ca. 5 m
- Dimensions (Ø x H without screw thread): ca. 62 mm x 21 mm

Microsoft Sensor and Location Platform ([Website](#))

- Profit from Windows applications (e.g. weather, maps, etc)
- Supporting the GNSS location platform API (32 bit)

Rendszerkövetelmények

- Windows Vista/7/8/8.1/10, Linux Kernel 2.6
- MD6 connection cable

A csomag tartalma

- MD6 serial receiver
- Mounting material: stainless steel nut and washer
- Navilock support CD incl. driver and user manual

Képek



General

Protection class:	IPX7
Suitable for outdoor:	yes

Interface

Connector:	1x MD6 serial
------------	---------------

Technical characteristics

Operating voltage:	5 - 48 V DC
Chipset:	u-blox NEO-M8U
Frequency range:	BEIDOU: B1, 1561.0980 MHz GALILEO: L1 1575.4200 MHz GLONASS: G1, 1.6025625 - 1.6155000 GHz GPS: L1, 1,5754200 GHz
Operating temperature:	-20 °C ~ 60 °C
Current consumption:	45 mA
Sensitivity:	-160 dBm
Update rate:	up tp 20 Hz

Physical characteristics

Housing colour:	white
Cable colour:	black
Cable length incl. connectors:	5 m
Diameter:	62 mm
Height:	21 mm

Manufacturer information

Utca	Beeskowdamm 13/15
Irányítószám	14167
Város	Berlin
Ország	Deutschland

E-mail	info@navilock.de
Weboldal	www.navilock.de